

Principal dimensions (mm)			Basic load ratings (kN)		Pu	Speed ratings (rpm)		Bearing+ Withdrawal	Designation		Dimensions (mm)													Abutment and fillet dimensions			Value			
基本尺寸			基本额定负荷		疲劳负荷极限	额定转速		轴承+ 退卸套	型号		尺寸													安装尺寸			计算系数			
d ₁	D	B	dyc	stc		Speed Ratings	Limiting Speed		Bearing	Withdrawal sleeves	d ₁	d ₂	D1	B ₁	B ₂ ¹⁾	G	G ₁	b	k	r _{1,2}		d _s	Da	r _s	e	Y1	Y2	Y _o		
			Cr	Cor								~	~							Min	Max								Max	Max
150	340	114	1600	1960	160	1500	1900	56.0	*22332CCKW/33	AH2332G	150	200	282	140	146	M170	24	16.7	9	4	177	323	3	0.35	1.9	2.9	1.8			
160	310	86	1120	1460	132	1900	2600	31.0	*22234CCKW/33	AH3134G	160	203	267	104	109	M180	16	16.7	9	4	187	293	3	0.27	2.5	3.7	2.5			
160	360	120	1760	2160	176	1400	1800	65.5	*22334CCKW/33	AH2334G	160	213	300	146	152	M180	24	16.7	9	4	187	343	3	0.33	2	3	2			
170	380	126	2000	2450	193	1300	1700	76.0	*22336CCKW/33	AH2336G	170	224	317	154	160	M190	26	22.3	12	4	197	363	3	0.35	1.9	2.9	1.8			
180	400	132	2120	2650	208	1200	1600	87.5	*22338CCKW/33	AH2338G	180	236	333	160	167	M200	26	22.3	12	5	210	380	4	0.35	1.9	2.9	1.8			
190	420	138	2320	2900	224	1200	1500	100	*22340CCKW/33	AH2340	190	248	351	170	177	Tr220	30	22.3	12	5	220	400	4	0.33	2	3	2			
200	460	145	2700	3450	260	1000	1400	130	*22344CCKW/33	AOH2344	200	279	389	181	189	Tr240	30	22.3	12	5	240	440	4	0.31	2.2	3.3	2.2			
220	500	155	3100	4000	290	950	1300	165	*22348CCKW/33	AOH2348	220	303	423	189	197	Tr260	30	22.3	12	5	260	480	4	0.31	2.2	3.3	2.2			
220	500	155	3100	4000	290	950	1300	165	*22348CCKW/33	AOH2348	220	303	423	189	197	Tr260	30	22.3	12	5	260	480	4	0.31	2.2	3.3	2.2			
260	540	165	3550	4550	325	850	1100	205	*22352CCKW/33	AOH2352G	260	328	458	205	213	Tr280	30	22.3	12	6	286	514	5	0.31	2.2	3.3	2.2			
280	580	175	4000	5200	365	800	1100	245	*22356CCKW/33	AOH2356G	280	354	492	212	220	Tr300	30	22.3	12	6	306	554	5	0.30	2.3	3.4	2.2			